



**WILDPEAK A/T TRAIL  
Q3 PROMO**



**WILDPEAK A/T TRAIL  
RUGGED CROSSOVER CAPABILITY ENGINEERED FOR ADVENTURE**



# EXTRA \$3 PER TIRE BONUS!

**GIVE YOUR CUSTOMERS RUGGED CROSSOVER CAPABILITY PLUS EARN AN ADDITIONAL \$3 PER TIRE! LIMITED TIME OFFER - VALID 07/01/2022 - 9/30/2022**

**EARN UP TO \$10.50 FOR EVERY A/T TRAIL WITH THE NEW FANATIC PRO LEVEL! →**

FALKEN TIRES PAYOUT LEVEL	FAN-LIMITED 30 UNITS	FAN-LITE 60 UNITS	FAN 125 UNITS	FAN+ 250 UNITS	FANATIC 400 UNITS	FANATIC PRO 600 UNITS
\$ REWARD PER A/T TRAIL UNIT	<del>\$2</del> \$5	<del>\$3</del> \$6	<del>\$4</del> \$7	<del>\$5</del> \$8	<del>\$6</del> \$9	<del>\$7.50</del> <b>\$10.50</b> NEW LEVEL!



## OFF-ROAD ADVENTURE FOR CROSSOVERS

Finally, an all-terrain tire made specifically for CUV's. Durable 2-ply polyester construction and rugged upper sidewall features protect the WILDPEAK A/T TRAIL from sharp rocks and off-road terrain, so you can take your crossover anywhere.

## SEVERE SNOW RATED

The WILDPEAK A/T TRAIL's increased tread depth and 3D Canyon Sipe Technology help provide more winter traction than a traditional All-Season tire. Backed by the USTMA's Severe Snow Rating, the A/T TRAIL helps crossover owners discover true all-weather capability.



**Contact your sales representative or email [Fanatic@Falkentire.com](mailto:Fanatic@Falkentire.com) for more details.**

Restrictions may apply. Falken Tires reserves the right to modify, alter or change any of the program terms and conditions at its sole discretion, with or without notice to its dealers and associate dealers. Road Hazard Restrictions: Mounting and balancing not included and you may be charged applicable taxes, the cost of valve stems, and disposal fees. Available in US and Canada only.



# WILDPEAK A/T TRAIL

RUGGED CROSSOVER CAPABILITY ENGINEERED FOR ADVENTURE

## SPECIFICATIONS

Wheel Dia.	Item Number	Tire Size	Load ID	Service Desc.	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revolutions Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load Single / Dual (lbs)	Max Pressure (psi cold)	U.T.Q.G.
16"	28711481	205/70R16	SL	97H	5.0 - 7.0	6.0	27.3	8.2	770	10	25.8	1609	51	680-A-A
	28712681	215/65R16	XL	102H	6.0 - 7.5	6.5	27.1	8.6	783	11	28.0	1874	50	680-A-A
	28711100	215/70R16	SL	100H	5.5 - 7.0	6.5	27.8	8.8	757	10	26.9	1764	51	680-A-A
17"	28712729	215/60R17	SL	96H	6.0 - 7.5	6.5	27.2	8.8	777	11	27.8	1565	51	680-A-A
	28714782	215/65R17	SL	99H	6.0 - 7.5	6.5	28.0	8.6	756	11	28.9	1709	51	680-A-A
	28712762	225/55R17	XL	101V	6.0 - 8.0	7.0	26.8	9.2	788	11	29.8	1819	50	680-A-A
	28712728	225/60R17	SL	99H	6.0 - 8.0	6.5	27.7	9.0	764	11	29.3	1709	51	680-A-A
	28711775	225/65R17	SL	102H	6.0 - 8.0	6.5	28.6	8.9	741	11	30.0	1874	51	680-A-A
	28712725	235/55R17	XL	103V	6.5 - 8.5	7.5	27.2	9.7	777	11	32.0	1929	50	680-A-A
	28711717	235/60R17	SL	102H	6.5 - 8.5	7.0	28.1	9.6	753	11	32.6	1874	51	680-A-A
	28712790	235/65R17	XL	108H	6.5 - 8.5	7.0	29.2	9.4	729	11	35.1	2205	50	680-A-A
18"	28711768	245/65R17	SL	107H	7.0 - 8.5	7.0	29.5	9.8	719	11	37.9	2149	51	680-A-A
	28712889	225/55R18	SL	98V	6.0 - 8.0	7.0	27.6	9.2	763	11	29.8	1653	51	680-A-A
	28711826	225/60R18	SL	100H	6.0 - 8.0	6.5	28.7	9.0	737	11	30.2	1764	51	680-A-A
	28712825	235/50R18	SL	97V	6.5 - 8.5	7.5	27.3	9.6	768	11	32.4	1609	51	680-A-A
	28712817	235/55R18	SL	100V	6.5 - 8.5	7.5	28.1	9.7	750	11	33.3	1764	51	680-A-A
	28712816	235/60R18	XL	107H	6.5 - 8.5	7.0	29.3	9.4	721	11	34.2	2149	50	680-A-A
	28712815	235/65R18	SL	106H	6.5 - 8.5	7.0	30.2	9.4	702	11	36.8	2094	51	680-A-A
	28712811	245/60R18	SL	105H	7.0 - 8.5	7.0	29.7	9.8	714	11	36.4	2039	51	680-A-A
19"	28712845	255/55R18	XL	109V	7.0 - 9.0	8.0	28.9	10.5	730	11	37.5	2271	50	680-A-A
	28711822	255/65R18	SL	111H	7.0 - 9.0	7.5	31.1	10.2	683	11	41.2	2403	51	680-A-A
	28712955	225/55R19	SL	99V	6.0 - 8.0	7.0	28.8	9.2	730	11	33.1	1709	51	680-A-A
	28712970	235/55R19	XL	105V	6.5 - 8.5	7.5	29.1	9.8	723	11	34.6	2039	50	680-A-A
	28712814	245/55R19	SL	103V	7.0 - 8.5	7.5	29.7	9.9	709	11	35.3	1929	51	680-A-A
	28712943	255/55R19	XL	111V	7.0 - 9.0	8.0	30.0	10.5	704	11	37.5	2403	50	680-A-A
20"	28711813	255/60R19	SL	109H	7.0 - 9.0	7.5	31.1	10.3	680	11	39.5	2271	51	680-A-A
	28712026	245/50R20	SL	102V	7.0 - 8.5	7.5	29.8	9.9	704	11	37.5	1874	51	680-A-A
	28712946	255/50R20	XL	109V	7.0 - 9.0	8.0	30.1	10.4	697	11	39.9	2271	50	680-A-A
	28712950	255/55R20	XL	110V	7.0 - 9.0	8.0	31.0	10.5	680	11	40.1	2337	50	680-A-A
	28712011	265/50R20	XL	111V	7.5 - 9.5	8.5	30.6	11.0	688	11	41.4	2403	50	680-A-A

Never mix tires of different size, construction or type on an axle except for temporary use as a spare tire. Always refer to vehicle owners manual for proper tire fitment.